

Prehľad modelov a technická špecifikácia

Model	Motor	Výkon (HP)	Krút. m. (Nm)	Valce / objem	Prevodovka	Počet stupňov	Vývod. h.	Pneumatiky		Rozmery d/š/v (mm)	Hmot. (kg)
								Predné	Zadné		
584E+	SONALIKA 3100 FLT	47	230	3valec 2780 cm ³	T50 Carraro	12/12R	540/540E	9,5 – R20	340/85R28	3964/1735/2443	2600
804.4 FG	PERKINS 1104D-44T	75	307	4valec 4400 cm ³	ZF T-537 synchronizovaná mechanika	16/8R	540/540E	208/70R20	380/70R28	4140/1680/2150	3040
804 Lux CRD	PERKINS Comon Rail 854F-E34T	75	307	4valec 3400 cm ³	ZF 537 AL reverzná, synchronizovaná, 4-stupňová, s násobičom krútiaceho momentu pod zatažením	16/16R	430/540/750/1000	12,4-24	18,4-30	4210/1935/2725	3580
854E+	PERKINS 1104D-44T	84	368	4valec 4400 cm ³	T506 UP Carraro reverzná, synchronizovaná, (V+Z) 3 skupiny x 4 st.	12/12R 24/24R	540/540E	280/85R24	420/85R30	4112/1990/2720	3780
904E+	PERKINS 1104D-44T	92	393	4valec 4400 cm ³	T506 UP Carraro reverzná, synchronizovaná, (V+Z) 3 skupiny x 4 st.	12/12R 24/24R	540/540E	320/85R24	460/85R30	4112/1990/2720	3780
1054E+	PERKINS 1104D- 44TA	102	405	4valec 4400 cm ³	T506 UP Carraro reverzná, synchronizovaná, (V+Z) 3 skupiny x 4 st.	12/12R 24/24R	540/540E	320/5R24	460/85R30	4112/1990/2720	4120